



552530

(43) International Publication Date  
21 October 2004 (21.10.2004)


PCT

(10) International Publication Number  
**WO 2004/090475 A2**

- (51) International Patent Classification<sup>7</sup>: **G01F 1/00**
- (21) International Application Number:  
PCT/GB2004/001618
- (22) International Filing Date: 14 April 2004 (14.04.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0308446.4 14 April 2003 (14.04.2003) GB
- (71) Applicant (for all designated States except US): **SENTEC LIMITED** [GB/GB]; Brunswick House, 61-69 Newmarket Road, Cambridge CB5 8EG (GB).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **GLAUSER, Antony, Robert** [GB/GB]; Sentec Limited, Brunswick House, 61-69 Newmarket Road, Cambridge CB5 8EG (GB). **KNILL, Alexander, Charles** [GB/GB]; Sentec Limited, Brunswick House, 61-69 Newmarket Road, Cambridge CB5 8EG (GB).
- (74) Agent: **MAGUIRE BOSS**; 5 Crown Street, St. Ives, Cambridgeshire PE27 5EB (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: MAGNETIC FLOW TRANSDUCER AND FLOW METER INCORPORATING THE SAME



(57) Abstract: A magnetic transducer (109) for measuring the flow of a fluid (108) has electrodes (102) and an alternating magnetic field (107), an electrode (102) having lower noise energy at frequencies below 5Hz than an electrode comprising carbon or corrosion-resistant metal alloy. The noise characteristic of the electrode (102) at magnetic field frequencies around 1 Hz is lower than that of an electrode comprising carbon or corrosion-resistant metal alloy.

WO 2004/090475 A2



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*